

# Zento L-150 RF Tx/Rx

## RF - Tx/Rx (duo configuration)

### General Info

Family	Zento				
Body Size	Front			Side / Thickness	
	Slim	Normal	Large	Normal	Thick
Type	Radio Frequency (RF), Tx / Rx				

Performance	metric	imperial
Maximum distance*	1,6m	62.99in
Detection dist. on side*	0,8m	31.5in
Dimension		
Height	1,526m	60.08in
Width	0,506m	19.92in
Depth (thickness)	0,056m	2.2in
Approx. weight	9,1kg	20lbs
Electrical Requirements		
PSU	NA	
Power Consumption	150mA	
Max. Power Cons.	200mA	
Operating Temp.	0 - 40 °C	32 - 104 °F
Frequency Technology		
Technology	Radio Frequency (RF)	
Frequency Range	8.2MHz	

### Other

Antenna Safety	CB, UL/cUL
Emissions Safety	FCC/IC, CE
Materials Used	anodized aluminium frame, acrylic insert
Available Colours	white as default, any colour available

\*detection distance may vary, depends on **environment** and **tag type**. Reference data is based on 4x4 paper label tag test



without media insert

with media insert

**RF - Tx/Rx**
**RF - Alternating Field**
**AM - Acousto Magnetic**